

wineo

THAT'S FLOORING



wineo 1200

PURLINE ORGANIC FLOORING


**BEST INGREDIENTS  
FOR FAVOURITE PLACES**

# THAT'S FLOORING

## CONTENT

Favourite places	05
Healthy living	07
Best ingredients	08
Product advantages	11
Joints and structures	12
Product composition	14
<b>wineo 1200</b> wood	18
<b>wineo 1200</b> stone	28
Application areas	34
PERFECT FIT accessories	36
Service	37
Certifications	38
Technical data	40





**NATURALLY  
HEALTHY LIVING**

Hello Martha  
wineo 1200 wood XL | Elastic | PL076R  
wineo 1200 wood XL | Semi-Rigid | PLC076R  
wineo 1200 wood XXL Multi-Layer | Rigid | MLP076R

## A FAVOURITE PLACE

... offers more than just a welcoming appearance. **Family members** should feel completely at home here.

Whether you're cooking, working, playing or sleeping. You can't put a price on life's favourite places when it comes to healthy living. It's where you can completely relax. In residential homes, cafés or indeed retirement homes – wineo 1200 allows you to create favourite places that keep you healthy in discerning houses and buildings.



**NATURALLY  
SUSTAINABLE**

Let's go Max  
winea 1200 wood XL | Elastic | PL270R  
winea 1200 wood XL | Semi-Rigid | PLC270R  
winea 1200 wood XXL Multi-Layer | Rigid | MLP270R

## HEALTHY LIVING FROM THE GROUND UP

Modern airtight building methods combined with poor ventilation leads to harmful substances accumulating in the air. This can trigger allergies, asthma and other adverse health conditions. This is particularly true if the building products emit high levels of dust. Walls and floors are especially important here as they represent the majority of the room surfaces. This is why building specialists and health experts are focusing more on healthy living spaces.



**80 – 90 % of our lives we spend in enclosed spaces.**



**An adult takes 20,000 breaths every day, a child even more.**



**1/3 of all Europeans suffer with asthma or allergies.**



**Only 28% of all people have sufficient ventilation during winter.**

**THESE ARE  
THE FACTS**

# BEST INGREDIENTS FOR SUSTAINABLE FLOORING

The new generation of wineo PURLINE organic flooring combines sustainability with performance and impressive designs. This flooring helps keep the air free from harmful substances by excluding chlorine, plasticisers and solvents.

Our high-quality polyurethane floor covering is based on ecuran, a high-performance composite material, developed and manufactured by Windmöller. ecuran is manufactured primarily from plant-based oils such as canola oil or castor oil and naturally-occurring mineral components such as chalk. Every production stage is also stamped with the Made in Germany seal of approval.



## SUSTAINABILITY

because that's what we believe in

- with the high-performance composite material ecuran
- usage of renewable raw materials and natural fillers
- easy to dispose
- carbon-neutral production in Germany
- Environmentally award-winning (see pages 38 / 39)
- completely odour-neutral and promotes wellbeing



## HIGH-PERFORMANCE

for everyday use

- tested resilience
- for domestic through to light industrial use
- low lifecycle costs
- UV-resistant and temperature-stable
- outstanding residual indentation performance



## DESIGN DIVERSITY

because it catches the eye

- 140 decors across three collections
- 12 different formats
- for gluing and clicking in
- on the roll or as planks
- modern, colourful and creative designs
- authentic-looking surface
- all-round V4 joint (V4)



**NATURALLY  
STRONG**

Call me Tilda  
wineo 1200 wood XL | Elastic | PL086R  
wineo 1200 wood XL | Semi-Rigid | PLC086R  
wineo 1200 wood XXL Multi-Layer | Rigid | MLP086R



### DURABLE

wineo organic flooring is **resistant to staining** and scores with high resilience.



### EASY CARE

The polyurethane surface makes the organic flooring **easy to clean** and maintain.



### UV-RESISTANT

Ready for summer: PURLINE organic flooring has a high light fastness and **an excellent UV resistance**.



### NON-SLIP

The tested surface ensures **safety with every step**.



### SUITABLE FOR DAMP AREAS

In the **kitchen or bathroom**: PURLINE organic flooring shows its best side in every situation.



### SUITABLE FOR UNDERFLOOR HEATING

More comfort: Installed over underfloor heating, the organic flooring provides **additional cozy warmth**.



### LOW-EMISSION

Take a deep breath: PURLINE organic flooring emits **no harmful substances** into the atmosphere.



### ODOUR NEUTRAL

Please do not disturb: **no unpleasant odours**.



### BURNS CLEANLY

Even in the event of fire: there are **no toxic gases** and **minimal smoke**.



### QUIET

The soft surface ensures **pleasantly quiet acoustics**.



### WARM TO THE FEET

**The organic flooring feels pleasantly warm** and is perfect for lounging, playing and living.




### GENTLE ON THE ANKLES

**Health-conscious**: The elastic surface is gentle on the joints.

# ORGANIC FLOORING WITH WOODEN PLANK LOOK

The secret is in the joint. It gives the room depth and the flooring an authentic wooden plank effect. All wineo 1200 wood decors have a lacquered, all around V4 joint.



## wineo 1200

... has a range of different surfaces which make the stone and wooden decors extremely realistic.



Elegant wooden texture



Fine wooden texture



Soft texture



**NATURALLY  
UNIQUE**

This is Theo  
wineo 1200 stone XL | Elastic | PL115R  
wineo 1200 stone XL | Semi-Rigid | PLC115R  
wineo 1200 stone XL Multi-Layer | Rigid | MLP115R

# PRODUCT COMPOSITION

## ELASTIC ORGANIC FLOORING FOR GLUING



### 1 Top element

PU-top layer with surface structure, decor paper and stabilisation

### 2 Base layer

ecuran high-performance composite material

### 3 Backing

Integrated FleeceTEC-System for easy and comfortable installation

#### i

##### Application area

Perfectly suited for new constructions and prepared subsurfaces.

##### Special product features

- low structural height of 2.2 mm
- elastic floor covering

##### Installation options: Gluing

- gluing to the existing subsurface
- gluing onto silentPLUS underlay mat
- reduces walking noise in the room

##### Type of installation: floating

- installation on self-adhesive silentPREMIUM CONTRACT underlay mat
- quick, easy and clean

##### Subfloor

The surface must be permanently dry, load-bearing, dust free and even. (levelled out for gluing process)

##### Accessories / installation aids

- matching skirtings for all wineo decors (p36)
- silentPREMIUM, CONTRACT and silentPLUS underlay mats (p36)
- dolphin knife for easy and clean cuts

## SEMI-RIGID ORGANIC FLOORING FOR CLICKING IN



### 1 Top element

PU-top layer with surface structure, decor paper and stabilisation

### 2 Profile connection

Fold-down locking (wood)  
LocTec locking (stone)

### 3 Base layer

ecuran high-performance composite material

### 4 Backing

Integrated FleeceTEC-System for easy and comfortable installation

#### i

##### Application area

Perfectly suited for new construction projects or for installation on existing floor coverings as per DIN 18202.

##### Special product features

- low structural height of 5 mm
- Telegraphing function: Minor irregularities in the subfloor will not show up

##### Installation type: floating

- installation for clicking in
- quick, easy and tidy

##### Subfloor

The surface must be permanently dry, load-bearing, dust free and even.

##### Accessories / installation aids

- matching skirtings for all wineo decors (p36)
- silentRIGID underlay mat (p36)
- dolphin knife for easy and clean cuts



## MULTI-LAYER | RIGID ORGANIC FLOORING FOR CLICKING IN



### 1 Top element

PU-top layer with surface structure, decor paper & stabilisation with ecuran

### 2 Profile connection

Fold-Down locking (wood)  
LocTec locking (stone)

### 3 Core board

Swell-protected Aqua-Protect® HDF core board

### 4 Underlay

Integrated underlay SoundPROTECT for an impact sound reduction of up to 15dB

### i

#### Application area

Perfectly suited for new constructions or installation on existing floor coverings according to DIN 18202.

#### Special product features

- Telegraphing: Minor irregularities in the subfloor will not show up
- Install-Ready: integrated underlay mat cuts refurbishment times and reduces walking and impact sounds by up to 15 dB

#### Installation type: floating

- installation for clicking in

#### Subfloor

The surface must be permanently dry, load-bearing, dust free and even.

#### Accessories / installation aids

- matching skirtings for all wineo decors (p36)
- PE vapour barrier for installing on mineral subsurfaces
- saw or laminate cutter

More information is available in our installation guides: see [www.wineo.de](http://www.wineo.de)



# NATURALLY PROVEN

Hello Martha  
wineo 1200 wood XL | Elastic | PL076R  
wineo 1200 wood XL | Semi-Rigid | PLC076R  
wineo 1200 wood XXL Multi-Layer | Rigid | MLP076R



**NATURALLY  
AUTHENTIC**

Cheer for Lisa  
wineo 1200 wood XL | Elastic | PL097R  
wineo 1200 wood XL | Semi-Rigid | PLC097R  
wineo 1200 wood XXL Multi-Layer | Rigid | MLP097R

**wineo 1200** wood

## CONTEMPORARY WOODEN DESIGNS – PURE CREATIVITY

wineo 1200 wood – eight wooden designs in contemporary XL and XXL formats. An elegant selection for unique designs. The lacquered, all round V4 joint emphasises the authentic wooden plank effect. It creates a cosy atmosphere and better place wherever it is used.

wood XL

Elastic

1500 × 250 × 2,2 mm



Semi-Rigid

1507 × 246 × 5 mm



wood XXL

Multi-Layer | Rigid

1845 × 237 × 9 mm



# wineo 1200 wood

<b>Installation type:</b>	Glue   Elastic	Click   Semi-Rigid	Click   Multi-Layer   Rigid
<b>Format:</b>	1500 × 250 mm	1507 × 246 mm	1845 × 237 mm
<b>Product thickness:</b>	2,2 mm	5 mm	9 mm
<b>Planks / Box:</b>	14/5,25 m <sup>2</sup>	6/2,22 m <sup>2</sup>	5/2,19 m <sup>2</sup>



Installed area **Welcome Oskar** | [PL269R](#) – [PLC269R](#) – [MLP269R](#) | lacquered, all-round joint (V4)



**Welcome Oskar** | [PL269R](#) – [PLC269R](#) – [MLP269R](#) | Fine wooden texture | lacquered, all-round joint (V4)



Installed area **Cheer for Lisa** | [PL097R](#) – [PLC097R](#) – [MLP097R](#) | lacquered, all-round joint (V4)



**Cheer for Lisa** | [PL097R](#) – [PLC097R](#) – [MLP097R](#) | Fine wooden texture | lacquered, all-round joint (V4)



## QUIET SPACE


**Welcome Oskar**  
 wineo 1200 wood XL | Elastic | [PL269R](#)  
 wineo 1200 wood XL | Semi-Rigid | [PLC269R](#)  
 wineo 1200 wood XXL Multi-Layer | Rigid | [MLP269R](#)

# wineo 1200 wood

<b>Installation type:</b>	Glue   Elastic	Click   Semi-Rigid	Click   Multi-Layer   Rigid
<b>Format:</b>	1500 × 250 mm	1507 × 246 mm	1845 × 237 mm
<b>Product thickness:</b>	2,2 mm	5 mm	9 mm
<b>Planks/Box:</b>	14/5,25 m <sup>2</sup>	6/2,22 m <sup>2</sup>	5/2,19 m <sup>2</sup>



Installed area Smile for Emma | [PL084R](#) – [PLC084R](#) – [MLP084R](#) | lacquered, all-round joint (V4)



Smile for Emma | [PL084R](#) – [PLC084R](#) – [MLP084R](#) | Fine wooden texture | lacquered, all-round joint (V4)



Installed area Call me Tilda | [PL086R](#) – [PLC086R](#) – [MLP086R](#) | lacquered, all-round joint (V4)



Call me Tilda | [PL086R](#) – [PLC086R](#) – [MLP086R](#) | Fine wooden texture | lacquered, all-round joint (V4)



**FAMILY  
AREA**

Smile for Emma  
 wineo 1200 wood XL | Elastic | [PL084R](#)  
 wineo 1200 wood XL | Semi-Rigid | [PLC084R](#)  
 wineo 1200 wood XXL Multi-Layer | Rigid | [MLP084R](#)

# wineo 1200 wood

<b>Installation type:</b>	Glue   Elastic	Click   Semi-Rigid	Click   Multi-Layer   Rigid
<b>Format:</b>	1500 × 250 mm	1507 × 246 mm	1845 × 237 mm
<b>Product thickness:</b>	2,2 mm	5 mm	9 mm
<b>Planks / Box:</b>	14/5,25 m <sup>2</sup>	6/2,22 m <sup>2</sup>	5/2,19 m <sup>2</sup>



Installed area **Announcing Fritz** | PL271R – PLC271R – MLP271R | lacquered, all-round joint (V4)



**Announcing Fritz** | PL271R – PLC271R – MLP271R | Elegant wooden texture | lacquered, all-round joint (V4)



Installed area **Let's go Max** | PL270R – PLC270R – MLP270R | lacquered, all-round joint (V4)



**Let's go Max** | PL270R – PLC270R – MLP270R | Elegant wooden texture | lacquered, all-round joint (V4)



## KITCHEN OASIS

**Announcing Fritz**  
 wineo 1200 wood XL | Elastic | PL271R  
 wineo 1200 wood XL | Semi-Rigid | PLC271R  
 wineo 1200 wood XXL Multi-Layer | Rigid | MLP271R

# wineo 1200 wood

<b>Installation type:</b>	Glue   Elastic	Click   Semi-Rigid	Click   Multi-Layer   Rigid
<b>Format:</b>	1500 × 250 mm	1507 × 246 mm	1845 × 237 mm
<b>Product thickness:</b>	2,2 mm	5 mm	9 mm
<b>Planks/Box:</b>	14/5,25 m <sup>2</sup>	6/2,22 m <sup>2</sup>	5/2,19 m <sup>2</sup>



Installed area Hello Martha | [PL076R](#) – [PLC076R](#) – [MLP076R](#) | lacquered, all-round joint (V4)




Hello Martha | [PL076R](#) – [PLC076R](#) – [MLP076R](#) | Elegant wooden texture | lacquered, all-round joint (V4)



Installed area Say hi to Klara | [PL272R](#) – [PLC272R](#) – [MLP272R](#) | lacquered, all-round joint (V4)



Say hi to Klara | [PL272R](#) – [PLC272R](#) – [MLP272R](#) | Elegant wooden texture | lacquered, all-round joint (V4)



**COMMAND  
CENTRE**

Say hi to Klara  
 wineo 1200 wood XL | Elastic | [PL272R](#)  
 wineo 1200 wood XL | Semi-Rigid | [PLC272R](#)  
 wineo 1200 wood XXL Multi-Layer | Rigid | [MLP272R](#)



**NATURALLY  
BEAUTIFUL**

Presenting Karl  
 wineo 1200 stone XL | Elastic | PL118R  
 wineo 1200 stone XL | Semi-Rigid | PLC118R  
 wineo 1200 stone XL Multi-Layer | Rigid | MLP118R

**wineo 1200** stone

## STUNNING STONE DESIGNS FOR MAXIMUM IMPACT

wineo 1200 stone – four stone designs in contemporary XL tile format. When every day brings something different, format flooring is the answer.

stone XL

Elastic



1000 × 500 × 2,2 mm

Semi-Rigid



1000 × 500 × 5 mm

Multi-Layer | Rigid



913 × 488 × 9 mm

# wineo 1200 stone

<b>Installation type:</b>	Glue   Elastic	Click   Semi-Rigid	Click   Multi-Layer   Rigid
<b>Format:</b>	1000 × 500 mm	1000 × 500 mm	913 × 488 mm
<b>Product thickness:</b>	2,2 mm	5 mm	9 mm
<b>Planks/Box:</b>	12/6,00 m <sup>2</sup>	6/3,00 m <sup>2</sup>	5/2,23 m <sup>2</sup>



This is Theo | PL115R – PLC115R – MLP115R | Soft texture



Introducing Otto | PL116R – PLC116R – MLP116R | Soft texture



CREATIVE  
WORKSHOP

Introducing Otto  
 wineo 1200 stone XL | Elastic | PL116R  
 wineo 1200 stone XL | Semi-Rigid | PLC116R  
 wineo 1200 stone XL Multi-Layer | Rigid | MLP116R



## wineo 1200 stone


<b>Installation type:</b>	Glue   Elastic	Click   Semi-Rigid	Click   Multi-Layer   Rigid
<b>Format:</b>	1000 × 500 mm	1000 × 500 mm	913 × 488 mm
<b>Product thickness:</b>	2,2 mm	5 mm	9 mm
<b>Planks/Box:</b>	12/6,00 m <sup>2</sup>	6/3,00 m <sup>2</sup>	5/2,23 m <sup>2</sup>



Please meet Paula | [PL117R](#) – [PLC117R](#) – [MLP117R](#) | Soft texture



Presenting Karl | [PL118R](#) – [PLC118R](#) – [MLP118R](#) | Soft texture



CHILL-OUT  
AREA

Please meet Paula  
wineo 1200 stone XL | Elastic | [PL117R](#)  
wineo 1200 stone XL | Semi-Rigid | [PLC117R](#)  
wineo 1200 stone XL Multi-Layer | Rigid | [MLP117R](#)

# BEST INGREDIENTS FOR EVERY APPLICATION AREA

The perfect features for every application area. Be it high standards of hygiene, resilience or design required, wineo 1200 is always a perfect fit thanks to its many special benefits in all areas of application.

RECOMMENDED FOR  
**HOME + LIVING**

RECOMMENDED FOR  
**HOTEL + HOSPITALITY**


RECOMMENDED FOR  
**RETAIL + FAIR**

RECOMMENDED FOR  
**HEALTH + CARE**

RECOMMENDED FOR  
**PUBLIC + EDUCATION**

i

Detailed information on flooring solutions is available here:



**SOMEWHERE  
ELSE**

**This is Theo**  
wineo 1200 stone XL | Elastic | PL115R  
wineo 1200 stone XL | Semi-Rigid | PLC115R  
wineo 1200 stone XL Multi-Layer | Rigid | MLP115R

**Call me Tilda**  
wineo 1200 wood XL | Elastic | PL086R  
wineo 1200 wood XL | Semi-Rigid | PLC086R  
wineo 1200 wood XXL Multi-Layer | Rigid | MLP086R

# PERFECT FIT ACCESSORIES

## UNDERLAY MATERIAL

We recommend using our polyurethane underlay material with wineo 1200. The basis is provided by ecuran, a high-performance composite material that is manufactured primarily from plant-based oils such as canola oil or castor oil and naturally-occurring mineral components such as chalk.

- fast, energy-efficient distribution of ground heat
- excellent noise reduction with hard and soft floor coverings
- long-life performance of at least 30 years
- outstanding residual indentation behaviour
- sustainable raw materials
- without chlorine, plasticisers or solvents



If a wineo PERFECT FIT PU underlay is used with a compatible wineo flooring product, the wineo warranty is extended by 5 years.



Detailed information can be found in our accessories brochure Art.-no. 20091021.

Download now:



## SKIRTINGS

- decor matching MDF skirtings for all wineo floor coverings and universally usable skirtings MDF as well as plastic /aluminium
- installation heights from 60mm to 100mm
- plastic mounting clips included in the range of accessories; alternatively glue or tack
- self-adhesive corner elements for easy installation



## PROFILES

- Comfort Profiles (self-adhesive profiles) for DIYers
- Premium Profiles (screwable profiles) for professionals
- profile types for different applications: Transition-, Adjustment and End profiles, L-End profiles, expansion joint profile, Angle profiles and stair nosing profiles

# SERVICE



## WINEO WEBSITE

Much more interesting and helpful information is available on our website

**www.wineo.de:**

- dealer portal with direct ordering option
- our top reference projects
- tender specifications
- technical data sheets
- cleaning and installation instructions
- find a dealer
- video portal with lots of tips
- newsletter registration

## SOCIAL MEDIA

Inspiration and product-specific knowledge in exciting short articles – you can discover under:

- Instagram
- facebook
- YouTube
- Pinterest
- LinkedIn

## WINEO FLOOR VIEWER

Any wineo floor can be simulated in your own home in an instant with our wineo Floor Viewer. The ideal way to choose the perfect flooring for you.

Test the wineo Floor Viewer now at **floorviewer.wineo.de**

# GUARANTEED HEALTHY LIVING

## Environmental certifications



### cradle to cradle®

The cradle to cradle® certification confirms the utilisation of environmentally safe, healthy and reusable materials (technical reutilisation) and the use of solar power or other regenerative sources of energy, together with responsible water stewardship and strategies adopted by a company to embrace its responsibility to society.



[www.blauer-engel.de/uz120](http://www.blauer-engel.de/uz120)


[www.blauer-engel.de/uz156](http://www.blauer-engel.de/uz156)

[www.blauer-engel.de/uz176](http://www.blauer-engel.de/uz176)

### Blue Angel (Blauer Engel)

The "Blue Angel" guarantees that our products and services fulfil high requirements placed on environmental, health and usage properties.

Criteria are compiled for each product group, which are checked every three to four years by the Federal Environment Agency.



### Austrian eco-label (Österreichisches Umweltzeichen)

The "Österreichisches Umweltzeichen" (Austrian eco-label) assesses products from quality, health-related and ecological standpoints. Basically, products can only be certified if they are harmless health-wise. The fulfilment of the criteria is checked every four years.



### Greenguard

The Greenguard certificate ensures that a product fulfils the strictest and most comprehensive requirements for emissions of Volatile Organic Compounds (VOCs) into the air.



**Declare.**

### Declare

Voluntary self-disclosure programme aimed at transforming the building materials industry into a healthier and more environmentally friendly product through transparency of ingredients used. By participating in Declare, manufacturers are obligated to disclose all ingredients.



### M1

Just like the "Blue Angel" quality mark in Germany, the M1 seal in the Finnish market labels our products as environmentally friendly, health-friendly and consumer-friendly. The focus is on emissions of Volatile Organic Compounds (VOCs).



### A+

Just like the "Blue Angel" in Germany, the A+ seal identifies our products as ecological, healthy and user-friendly in the French market.



### TFI-TÜV PROFICERT PREMIUM for Multi-Layer

The TFI (Textiles & Flooring Institute GmbH) and the TÜV Hessen evaluate products based on qualitative, health and ecological principals. Fundamentally, only products that are considered harmless to health can be certified.



### KfB

Award from the competence centre for dynamic processes at Bielefeld University of Applied Sciences (FH). The flooring product Purline has passed the dynamic standard examination of rolling behaviour in accordance with the KfB roadmap.



## Environmental certifications



### eco-bau Switzerland (eco-bau Schweiz)

Eco-Bau assesses the ecological aspects of building materials and services. It encompasses all of the significant environmental effects during the entire lifespan of the materials. The assessment is made on the basis of the following criteria: conservation of natural resources, energy for producing materials, solvent emissions, presence of environmentally and health-damaging components, emission of heavy metals and other damaging substances.



### FloorScore®

With SCS Global Services' FloorScore® certificate program manufacturers of floor coverings can assess the conformity of their products with the emission requirements in the U.S. but also worldwide utilized building evaluation systems, such as LEED clearly.



## Building certification / Product declaration



### BREEAM

The British sustainability certificate for development projects is used in 15 other countries.



### DGNB

Certification system of the German Sustainable Building Council and the Federal Ministry of Transport, Building and Urban Affairs. Evaluates a building's quality over its entire life cycle and is internationally applicable.



### LEED

Rating system of the US Green Building Council. It considers the regional and local criteria according to global standards. The use of building materials with cradle to cradle proof is evaluated with bonus points.



### WELL

The WELL Building Standard (WELL) focuses on health and well-being of the people within in the building.



### EPD

The environmental product declarations is a transparency tool for the sustainability valuation of products. It is the basis for sustainability calculations for buildings.



## Information platforms



### Sentinel Haus Institut

The Sentinel Haus Institut is a leading engineering service provider and knowledge leader for more healthy building, refurbishment and renovation.









### Heinze

Germany's leading information platform for building products, company profiles and architectural projects.



**SUSTAINABLE FOR NATURE.  
WELLBEING FOR PEOPLE.**

# NATURALLY HIGH-PERFORMANCE


wineo 1200	wood XL   Elastic	wood XL   Semi-Rigid	wood XXL Multi-Layer   Rigid	stone XL   Elastic	stone XL   Semi-Rigid	stone XL Multi-Layer   Rigid
Installation type	 to glue	 to click	 to click	 to glue	 to click	 to click
Locking	-	Fold-Down	Fold-Down	-	LocTec	LocTec
Utilization classes	23/33/42	23/33	23/33	23/33/42	23/33	23/33
Format	1500 × 250 mm	1507 × 246 mm	1845 × 237 mm	1000 × 500 mm	1000 × 500 mm	913 × 488 mm
Product thickness	2,2 mm	5 mm	9 mm	2,2 mm	5 mm	9 mm
Content / box	14 / 5,25 m <sup>2</sup>	6 / 2,22 m <sup>2</sup>	5 / 2,19 m <sup>2</sup>	12 / 6,00 m <sup>2</sup>	6 / 3,00 m <sup>2</sup>	5 / 2,23 m <sup>2</sup>
Boxes / pallet	56 / 294,00 m <sup>2</sup>	48 / 106,77 m <sup>2</sup>	48 / 105,12 m <sup>2</sup>	50 / 300,00 m <sup>2</sup>	36 / 108,00 m <sup>2</sup>	34 / 75,82 m <sup>2</sup>
Weight	~ 3,00 kg / m <sup>2</sup>	~ 9,00 kg / m <sup>2</sup>	~ 9,10 kg / m <sup>2</sup>	~ 3,00 kg / m <sup>2</sup>	~ 9,00 kg / m <sup>2</sup>	~ 8,90 kg / m <sup>2</sup>
Staining / chemical resistance EN ISO 26987	very good resistance with regards to concentration and exposure time					
Reaction to fire   EN 13501-1				C <sub>fl</sub> - s1		
Anti slip category   DIN 51130				R9		
Light fastness   EN ISO 105-B02				~ 7		
Residual indentation   EN ISO 24343-1				≤ 0,10 mm		
Dimensional stability   EN ISO 23999	≤ 0,15 %	≤ 0,15 %	-	≤ 0,15 %	≤ 0,15 %	-
Underfloor heating	Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.					
Thermal resistance   ISO 8302	~ 0,01 (m <sup>2</sup> K)/W	~ 0,01 (m <sup>2</sup> K)/W	~ 0,06 (m <sup>2</sup> K)/W	~ 0,01 (m <sup>2</sup> K)/W	~ 0,01 (m <sup>2</sup> K)/W	~ 0,06 (m <sup>2</sup> K)/W
Castor chair test   EN ISO 4918   EN 425	25000 revolutions – no damage with rolls type W					
Impact sound reduction   EN ISO 10140	~ 4 dB	~ 4 dB	~ 15 dB	~ 4 dB	~ 4 dB	~ 15 dB
Effect of a furniture leg   EN 424	Foot Type 2 – no damage		-	Foot Type 2 – no damage		-
Anti-static properties   EN 1815				≤ 2 kV		
Guarantee for private use according to Windmoeller guarantee conditions				30 years		
Guarantee extension when installed on PU underlays	+5 years	+5 years	already integrated	+5 years	+5 years	already integrated



Utilisation class 23:  
Domestic area with  
intensive usage



Utilisation class 33:  
Commercial sector  
with heavy usage



Utilisation class 42:  
Light industry sector  
with regular usage

**MADE IN GERMANY**





## THE BEST QUALITY FOR OVER 70 YEARS

For us, outstanding quality means more than an excellent product. As a family business in its 3rd generation we carry a high level of social and ecological responsibility. That's why we always provide you with the greatest possible level of transparency. And therefore even more safety.

- many quality controls from the initial mixing of the ingredients to the completion stage
- traceability of the exact time of production via a reverse-side overprint
- outstanding attributes regarding durability, maintenance and safety

**MADE IN GERMANY**

Windmüller GmbH

Nord-West-Ring 21

D-32832 Augustdorf

Tel.: +49 (0) 52 37 609 - 0

Fax: +49 (0) 52 37 609 - 309

info@wineo.de

[www.wineo.de](http://www.wineo.de)

Handed over by:

Product no. 20096079 | 01/2021

Member of

**FEB** **ERFMI.** **DGNB** m  
m  
f  
a

# wineo