

DESCRIPTION

DESCRIPTION			ELITE
Surface			X PUR scuff-resistant surface
Backing			Combined closed cell foam system
Thickness	mm	EN ISO 24346	6,0
Top layer	mm	EN ISO 24340	0,9
Weight	g/m ²	EN ISO 23997	3250
Width	m	EN ISO 24341	2
Standard roll length	kg/m ²	EN ISO 24341	20 ± 10%

CLASSIFICATION

Product specification		EN 14904	Vinyl indoor sports floor (category P1)
Impact sound insulation	dB	EN ISO 717-2	21
Thermal resistance	m ² K/W	EN 685	0,06
Reaction to fire	-	EN 13501	C _{ii} -s1

SPORT PROPERTIES

Friction	-	EN 13036-4	80-110
Shock absorption	%	EN 14808	≥ 25 (P1)
Vertical deformation	mm	EN 14809	1
Ball rebound	%	EN 12235	98
Specular gloss	%	EN 2813	< 30

TECHNICAL CHARACTERISTICS

Dimensional stability	%	EN ISO 23999	± 0,2
Indentation resistance	mm	EN 1516	< 0,5
Resistance to rolling load	N	EN 1569	1500
Colour fastness	-	EN 13036-4	6
Chemical resistance	-	EN ISO 26987	- no change
Abrasion resistance	mg/1000 cycles	EN ISO 5470-1	< 250

OTHERS



1360

3096

3338

4289

7483



6170



2519



NO WAX



SOLVENT FREE



MINIMIZE THE GROWTH OF MICROORGANISMS

15 years

Limited warranty



No periodic renewal needed

Solvent and heavy metal free



GRABOPLAST LTD.

H-9023 Győr, Fehérvári út. 16/b. Telefon: (+36) 96 506-100
[instagram.com/graboplast](https://www.instagram.com/graboplast) | [facebook.com/graboplast](https://www.facebook.com/graboplast)
www.grabo1905.com

